


(11)Publication number : 09-135478  
(43)Date of publication of application : 20.05.1997

(51)Int.Cl.	H04Q 7/38
	H04H 1/00
	H04H 5/00

(21)Application number : **07-293015** (71)Applicant : **SANYO ELECTRIC CO LTD**  
(22)Date of filing : **10.11.1995** (72)Inventor : **TACHIBANA HIROYUKI**  
**MATSUI TAKEHARU**  
**MITSUFUJI HIRONORI**  
**SATA MASAHIRO**

(57)Abstract:

**SOLUTION:** The FM multiplex signal received by an antenna 12 and FM demodulated by an FM tuner part 14 is inputted to an FM multiplex decode part 15 and a base band signal is extracted. Based on the extracted base band signal, a CPU 40 at a personal computer 120 reconstitutes the program data. In that case, each time the page data are completely received, the time of reception end is possessed from a timer 50 and the contents of page data and the time of reception end are correspondently stored in a memory part 44. The CPU 40 correspondently displays the page data and the reception



## LEGAL STATUS

[Date of request for examination] 23.07.1999

[Date of sending the examiner's decision of rejection] 03.04.2001

[Kind of final disposal of application other than the examiner's decision of rejection or application converted registration]

[Date of final disposal for application]

[Patent number]

[Date of registration]

[Number of appeal against examiner's decision of rejection]

[Date of requesting appeal against examiner's decision of rejection]

[Date of extinction of right]